



Technical Data

Supply voltage	5 V DC ± 500mV
Current consumption (average)	0 mA
Rated switch current	50 mA
Ambient temperature during operation	0 °C to +30 °C
Ambient temperature during storage and transport	-40 °C to +60 °C
Cable length (including loop)	1800 mm ± 50mm
Dimensions (l x w x h)	30.4mm x 67.8mm x 20.5mm
Degree of protection	IP20
Compatible motor control boxes	S1 (firmware version 1.8 or higher)

This drawing don't subject to the revision service.														
Without our specifically acceptance, this drawing is not allowed to be copied or given to other persons.	scale: drawing not in scale	position:												
<table border="1"> <thead> <tr> <th></th> <th>date</th> <th>name</th> </tr> </thead> <tbody> <tr> <td>edited</td> <td>21.08.2018</td> <td>V.Skeljic</td> </tr> <tr> <td>check.</td> <td>19.09.2018</td> <td>S.Lägeler</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> </tbody> </table>		date	name	edited	21.08.2018	V.Skeljic	check.	19.09.2018	S.Lägeler				Handswitch for instalation in the desktop Up/Down Button	
	date	name												
edited	21.08.2018	V.Skeljic												
check.	19.09.2018	S.Lägeler												
Bansbach easylift GmbH Barbarossastr. 8 D-73547 Lorch/Württemberg	EEL-LDH-BASIC-IL													
	sheet													