



Technical Data

| | |
|--|-------------------------------------|
| Supply voltage | 5 V DC ± 200mV |
| Average power consumption | 60 mA |
| Average power consumption in standby mode | 1.3 mA |
| Ambient temperature during operation | 0 °C to +30 °C |
| Ambient temperature during storage and transport | -40 °C to +60 °C |
| Cable length | 2000 mm ± 40mm |
| Dimensions (l x w x h) | 42.0mm x 95.4mm x 17.3mm |
| Degree of protection | IP20 |
| Compatible motor control boxes | S1 (firmware version 1.9 or higher) |

| This drawing don't subject to the revision service. | | | | | | | |
|--|---|------------|------|------|------------|----------|------------|
| Without our specifically acceptance, this drawing is not allowed to be copied or given to other persons. | scale: drawing not in scale | position: | | | | | |
| | <table border="1"> <thead> <tr> <th>date</th> <th>name</th> </tr> </thead> <tbody> <tr> <td>22.08.2018</td> <td>V.Skeljc</td> </tr> <tr> <td>19.09.2018</td> <td>S.Lägeler</td> </tr> </tbody> </table> | | date | name | 22.08.2018 | V.Skeljc | 19.09.2018 |
| date | name | | | | | | |
| 22.08.2018 | V.Skeljc | | | | | | |
| 19.09.2018 | S.Lägeler | | | | | | |
| Handswitch with integrated display for instalation in the desktop | | sheet | | | | | |
| 2 memorie positions + Up/Down | | | | | | | |
| Bansbach easylift GmbH Barbarossastr. 8 D-73547 Lorch/Württemberg | | EEL-LDH-IL | | | | | |